

TOROTEC 0W-20 LONGLIFE

Product Code: PCM046 | Revision: 20220907



Fully synthetic, low viscosity automotive engine oil for VW vehicles.

Available Pack Sizes



Applications

The latest generation fully synthetic and mid SAPS engine oil formulated for use with modern petrol and diesel engines, particularly vehicles in the VW Group. Utilising a combination of a unique additive technology and our specialist Adaptive Molecular Technology to maintain engine power, maximum efficiency and improves reliability whilst supporting exhaust after-treatment devices throughout the vehicle's lifecycle in mixed driving conditions.

Recommended by Aztec Oils as suitable for the following applications

ACEA C5
Porsche C20
VW 508.00/509.00

Benefits

- Advanced anti-wear technology helps to protect engine components.
- Compatible with diesel particulate filters (DPF) and three-way catalysts (TWC), including those utilising SCR technology.
- Contains a chemical marker as specifically required by VW.
- Excellent low temperature performance.
- Exceptional fuel economy.
- High performance with outstanding wear protection.
- Maintains very high standards of engine cleanliness.

Typical Test Data

Appearance		Clear & bright
Colour		Green/blue
Density @ 15°C (kg/m ³)	ASTM D4052	0.849
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	44
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	8.3
Pour Point (°C)	ASTM D97	-45
Total Base Number (mg KOH/g)	ASTM D2896	>6.0
Viscosity Index	ASTM D2207	167

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- When disposing of the product after use, please protect the environment and comply with local regulations.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.